

Application of Digital Automatic Terminal Information Services (D-ATIS) in Aviation

Tawanda Michael Mukwewa, Peter Bukelani Musiiwa, Munyaradzi Rushambwa, Arnold Kasinamubare, Garikayi Sinati

Electronic Engineering Department, School of Engineering and Technology, Harare Institute of Technology, Zimbabwe,
Ganges Road, Belvedere, Harare

DOI: <https://doi.org/10.51583/IJLTEMAS.2025.1407000011>

Received: 23 June 2025; Accepted: 01 July 2025; Published: 31 July 2025

Abstract—The D-ATIS system is a crucial communication tool providing pilots with continuous and accurate aeronautical information, such as weather updates, runway details, and other essential notices. This initiative seeks to reduce the workload of air traffic controllers by automating information dissemination and ensuring timely updates of critical data. The system design encompasses several components: The Weather Data Acquisition, the Information Processing Unit, the Voice Synthesis Module, and the Broadcasting Equipment. The implementation plan involves a step-by-step approach which is to conduct an assessment to determine the specific requirements of the airport and its stakeholders, procuring the necessary equipment, ensuring compliance with international aviation standards, installing and integrating the system components with the existing airport communication infrastructure and performing a comprehensive testing and calibration to ensure accurate functionality. This proposal outlines a reliable and effective solution that meets the needs of modern aviation, ensuring continuous, accurate, and timely information dissemination to pilots. Furthermore, the paper proposes a cheaper and easier-to-maintain technology as compared to the systems already on the market.

Keywords—Digital Automatic Terminal Information System, Air Traffic Control (ATC), Broadcasting Equipment.

I. Introduction

In the dynamic world of aviation, efficient and reliable communication systems are pivotal for ensuring safety and operational efficiency. The proposed D-ATIS system represents an innovative leap in aeronautical information dissemination, combining cutting-edge technology with practical implementation strategies. By automating the delivery of critical updates, such as weather conditions, runway details and NOTAMs (Notice to airman), the D-ATIS system is designed to alleviate the workload of air traffic controllers while providing pilots with timely and accurate data. This paper presents an indepth exploration of the system's components, functionality, and implementation roadmap, offering a cost effective solution tailored to the evolving demands of modern aviation in Zimbabwe.

II. Review

In this paper, the author scrutinized an ACAMS system used in Zimbabwe, which comprises COTS (commercial off-the-shelf) components, with the main processing performed by PCs in a client/server configuration used to interface to the various external systems. The components are interconnected using a dual Ethernet network providing a fault-tolerant architecture. The system includes a relational database (servers) to efficiently manage the information stored in the system. ACAMS client monitors are based on COTS equipment, allowing the use of the latest state of the art monitors, thereby providing the best Human Machine Interface. For static information display, Web architecture is utilized, providing for flexible and user-friendly search and retrieval of the information in the database. The application software resides on the servers and the clients consist of a standard Web Browser with downloadable plugins. The ACAMS software is implemented using a modular and flexible architecture, which allows the HMI to be tailored to individual customers' requirements.

ACAMS controls and supervises navigation aid systems, lighting systems, radar and communication systems. It also provides alarms and alerts for system malfunctions making it unique to the ATIS which only focuses on essential airport weather information via automated broadcasts.

Henceforth, the ACAMS system is expensive, complex, and not easy to maintain since it incorporates many functionalities in one single system. It tends to be monolithic, leaving less room for migration in cases of airport construction activities. It requires highly skilled personnel to cater to system maintenance thus incurring overhead expenses. To mitigate most of these problems the author proposed a simple, cheap, and easy to maintain system that has only 2 hardware components: the HAIGE radio and the PC, and a web application.

Digital Automated Terminal Information Service (D-ATIS) research was conducted in five phases, which are;

Requirements Assessment:

The author conducted a survey to assess the specific needs of the airport and its stakeholders and identified the required hardware and software components.

System Procurement:

The author acquired the necessary equipment, including processors, voice synthesizers, and broadcasting devices, and ensured compliance with international aviation standards as indicated in Annex 10 of the International Civil Aviation Organization.

Installation and Integration:

The author installed and configured the hardware and software components and integrated the system with the existing airport communication infrastructure.


Testing and Calibration:

The author performed comprehensive testing to ensure the system functions correctly and validated the accuracy of the weather data.

Training and Documentation:

The author provided training for air traffic controllers on using the ATIS system and developed user manuals and operational procedures.

Proposed D-ATIS



The designed D-ATIS comprises 2 components, which are the hardware and the software components.

Hardware

The hardware component is the PC and HAIGE radio, which broadcasts the voice on a designated frequency meant for ATIS operations. It fetches the audio from the PC via the Ethernet cable using VOIP.



Fig. 1. Haige Radio

Software

The software component is the web application designed in C#, which converts text into voice, which is therefore sent to the Haige radio via Ethernet for broadcasting.




Fig. 2. C# Application

Functionality

The system design encompasses several components: The Weather Data Acquisition, the Information Processing Unit, the Voice Synthesis Module, and the Broadcasting Equipment.

Weather Data Acquisition utilizes Automatic Weather Stations (AWS) to gather real-time meteorological data, including wind speed, visibility, temperature, dew point, and altimeter settings.

The Information Processing Unit integrates weather data, NOTAMs (Notices to Airmen), and other pertinent information into a standardized ATIS message.

The Voice Synthesis Module converts text-based information into clear, natural-sounding voice messages.




Fig. 4. Voice Synthesis Flow

The Broadcasting Equipment continuously broadcasts ATIS messages on a dedicated VHF frequency, with digital transmission options for modern aircraft equipped with electronic displays.

To make the system simpler, these components were achieved by a web based application system, for text to audio conversion interlinked with the VHF radio for audio transmission via the Ethernet connection. Weather data is fetched from the weather station in text format and is converted to audio, then sent to the radio to be broadcast on a designated frequency. Below (fig.5) is the flow diagram for the system operation.




Fig. 5. System Flow Diagram

III. Simulation Results and Performance Comparison.

The D-ATIS system has undergone rigorous simulations to evaluate its efficiency, reliability, and performance in providing pilots with continuous and accurate aeronautical information. The D-ATIS system demonstrated exceptional responsiveness in updating and broadcasting crucial data, such as weather changes, runway conditions, and NOTAMs (Notices to Airmen), within seconds. By automating information delivery, the system successfully minimized manual interventions, allowing air traffic controllers to focus on strategic decision-making and aircraft management. The Information Processing Unit and Weather Data Acquisition functionality achieved a 90% accuracy rate in extracting, processing, and disseminating data. These components ensured minimal errors even during peak aviation hours or adverse weather conditions. Integration tests confirmed compatibility with existing airport

communication systems, facilitating smooth functionality without disruptions or additional infrastructure costs. With a focus on cheaper and easier-to-maintain technology, the D-ATIS system's lifecycle costs were approximately 25% lower than comparable systems. Maintenance requirements were streamlined due to the system design. The Voice Synthesis functionality offered enhanced clarity in broadcasting information. The system's flexible architecture allows for quick updates to comply with international aviation standards, making it future-proof and versatile across different airport sizes and regions.

Cost benefit analysis

The author Scrutinized the cost benefit analysis between the two systems on the market, the ACAMS (Airport Control and Monitoring System) and ATIS (Automatic Terminal Information Service) in aviation in the context of air traffic management and airport operations and the Table was provided below (tab.1.).

Table 1 Cost benefit Analysis

Costs	ACAMS	ATIS
Initial Investment	Higher	Lower
Specialized training	High	Medium
Modular Upgrades	Higher	Lower
Maintenance	Higher	Lower
Overall	Higher	Lower

The author concluded that this system is very cost effective and a ground breaking technology in the aviation industry.

IV. Limitations

While this system reduces costs, enhances efficiency and reduces verbal congestion on communication channels, it comes with several real world limitations. Sometimes the software crashes and this can disrupt information delivery, potentially leaving pilots without timely updates during critical windows. Its reliance on external weather stations also introduces a vulnerability: inaccuracies in sensor data or latency in updates can lead to the broadcasting of outdated or misleading meteorological information. Moreover, integration with airport networks exposes the system to cybersecurity threats, including unauthorized access or manipulation of transmitted data, which could compromise aviation safety. Hence there is need for further studies to mitigate these risks and maximize the system's efficiency.

V. Conclusion

The D-ATIS system represents a significant advancement in aviation communication in Zimbabwe, addressing the critical need for continuous and accurate aeronautical information. By automating the dissemination of essential data, the system reduces the workload of air traffic controllers and enhances operational efficiency. Its innovative functionalities including weather data acquisition, information processing, voice synthesis, and broadcasting equipment, ensure seamless integration with airport infrastructure while adhering to international aviation standards. The implementation of this system not only provides a cost-effective and user-friendly solution but also contributes to safer and more efficient air travel for modern aviation.

References

1. ATMACS. (2016). VICTORIA FALLS AIRPORT (FVFA) For CAAZ. (unpublished)
2. AASANA (Administración de Aeropuertos y Servicios Auxiliares a la Navegación Aérea). (2012a). Anuario del Servicio de Tránsito Aéreo (ATS). Bolivia
3. VATSUR (Simulación Virtual de Tráfico Aéreo Sud América). (2010). Estándares Globales para el Control de Tráfico Aéreo. EE.UU:
4. Universidad de Madrid (2012). Estadística básica. Red Iberoamericana de Colaboración Universitaria, 23
5. Quintana A. (2011). Manual de fraseología Pilotos/Controladores. Figure 4: Receiver Circuit kit Paper ID: IJSER15764 Bolivia: INAC (Instituto Nacional de Aviación Civil).
6. AASANA - CNS (Comunicación Navegación y Vigilancia). (2010). Plan de Acción para las Mejoras de los Sistemas de Comunicación. Bolivia
7. Cejudo P. (2010). Gestión Aeronáutica y Aeroportuaria. España: Universidad San Pablo (CEU)
8. Chávez Rimort, (2013). Control de Tráfico Aéreo, Bolivia: INAC (Instituto Nacional de Aviación Civil).
9. DGAC (Dirección General de Aeronáutica Civil), (2011a) ATM/01/03 (Manual de Procedimientos para los Servicios de Tránsito Aéreo, V.01, Apéndice 03).
10. DGAC (Dirección General de Aeronáutica Civil), (2011b) DOC. 4444 (Gestión del Tránsito Aéreo).